


ITECH C2 305 M DALI



Catalog number	TM-IT.C2DAM360W
Application	escape route lighting
Duration time	3 h
Operating mode	M
Version	DALI
Colour	RAL9003
Luminous flux	478 lm
Maximum light power (the luminaire can power the light source with a different power)	4.5 W
Active power	6 W
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	10-40 °C
Material	PC
Insulation class	2
IP	IP65
IK	IK06
Battery	LiFePO4/C 6.4V 3.0Ah
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Type - DALI	A - maintained, controllable, dimmable
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	8,9	19,8
3,0	10,1	22,7
4,0	12,6	28,2
5,0	14,2	33,0
6,0	15,4	37,2
7,0	14,6	40,5
8,0	10,5	33,2
9,0	5,8	29,0
10,0	5,2	27,0

