

ITECH F2

105 M DATA 2 COLD



Catalog number	TM-IT.F2DDM16CW
Application	escape route lighting
Duration time	1 h
Operating mode	M
Version	DD - DATA2
Colour	RAL9003
Luminous flux	499 lm
Maximum light power (the luminaire can power the light source with a different power)	4.5 W
Active power	6 W
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	-15-40 °C
Material	PC
Insulation class	2
IP	IP65
IK	IK06
Battery	LiFePO4/C 6.4V 3.0Ah
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
cold	yes
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	6,1	14,5
3,0	6,8	16,2
4,0	7,6	18,9
5,0	8,3	20,5
6,0	8,8	22,2
7,0	9,3	23,5
8,0	9,7	24,5
9,0	10,0	25,7
10,0	10,2	26,5

