



TM.ONTEC C C1 CB



Catalog number	TM-OC.C1CB0000C
Application	escape route lighting
Duration time	-
Operating mode	-
Version	for central battery
Colour	RAL3020
Luminous flux	297 lm
Maximum light power (the luminaire can power the light source with a different power)	3 W
Active power	4.5 W
Power supply	210+250 V AC
Power supply CB	186+254 V DC
Dimming mode	no
Temperature range	-15-55 °C
Material	PC
Insulation class	2
IP	IP20
IK	IK03
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Standards	PN-EN 60598-1, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height

2,5
3,0
4,0
5,0
6,0
7,0
8,0
9,0
10,0

Distance wall - fitting

9,5 - 1h/CB | 8,5 - 3h
11,0 - 1h/CB | 9,0 - 3h
13,0 - 1h/CB | 7,5 - 3h
13,5 - 1h/CB | 3,0 - 3h
10,5 - 1h/CB | 3,0 - 3h
5,0 - 1h/CB
3,0 - 1h/CB
4,0 - 1h/CB
/

Distance fitting - fitting

21,0 - 1h/CB | 19,0 - 3h
24,0 - 1h/CB | 21,0 - 3h
29,0 - 1h/CB | 23,0 - 3h
32,0 - 1h/CB | 20,0 - 3h
34,0 - 1h/CB | 14,0 - 3h
32,0 - 1h/CB
26,0 - 1h/CB
19,0 - 1h/CB
/

