


TM.ONTEC R C1 302 M DALI



Catalog number	TM-OR.C1DAM300B
Application	escape route lighting
Duration time	3 h
Operating mode	M
Version	DALI
Colour	RAL9005
Luminous flux	246 lm
Maximum light power (the luminaire can power the light source with a different power)	2 W
Active power	7.2 W
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	10-35 °C
Material	PC
Insulation class	2
IP	IP20
IK	IK03
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty	24 months - AT 36 months - ST 60 months - DATA, CB
Type - DALI	A - maintained, controllable, dimmable
Standards	PN-EN 60598-1, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	8,7	19,4
3,0	9,8	22,2
4,0	11,4	26,7
5,0	12,0	30,5
6,0	4,9	28,7
7,0	3,6	22,4
8,0	3,2	18,6
9,0		
10,0		

