



# TM.ONTEC R M5 05 CBA



|                                                                                       |                                                          |
|---------------------------------------------------------------------------------------|----------------------------------------------------------|
| Catalog number                                                                        | TM-OR.M5CBA000W                                          |
| Application                                                                           | anti-panic lighting                                      |
| Duration time                                                                         | -                                                        |
| Operating mode                                                                        | -                                                        |
| Version                                                                               | for central battery                                      |
| Colour                                                                                | RAL9003                                                  |
| Luminous flux                                                                         | 555 lm                                                   |
| Maximum light power (the luminaire can power the light source with a different power) | 4.5 W                                                    |
| Active power                                                                          | 8.2 W                                                    |
| Power supply                                                                          | 210+250 V AC                                             |
| Power supply CB                                                                       | 186+254 V DC                                             |
| Dimming mode                                                                          | yes                                                      |
| Temperature range                                                                     | -10-40 °C                                                |
| Material                                                                              | PC                                                       |
| Insulation class                                                                      | 2                                                        |
| IP                                                                                    | IP20                                                     |
| IK                                                                                    | IK03                                                     |
| Warranty                                                                              | 24 months - ST<br>36 months - AT<br>60 months - DATA, CB |





## PHOTOMETRY [m]

| Ceiling height | Distance wall - fitting | Distance fitting - fitting |
|----------------|-------------------------|----------------------------|
| 2,5            | 4,2                     | 8,9                        |
| 3,0            | 4,7                     | 10,3                       |
| 4,0            | 5,7                     | 13,0                       |
| 5,0            | 6,4                     | 15,0                       |
| 6,0            | 6,6                     | 17,0                       |
| 7,0            | 7,0                     | 19,0                       |
| 8,0            | 7,0                     | 20,0                       |
| 9,0            | 6,9                     | 21,2                       |
| 10,0           | 6,9                     | 22,0                       |

