


ONTEC S F2 05 CBA



Catalog number	TM-OS.F2CBA060W
Application	escape route lighting
Duration time	-
Operating mode	-
Version	for central battery
Colour	RAL9003
Luminous flux	439 lm
Maximum light power (the luminaire can power the light source with a different power)	4.5 W
Active power	7.0 W
Power supply	210+250 V AC
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	-10-40 °C
Material	PC
Insulation class	2
IP	IP65
IK	IK08
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	6,3	15,0
3,0	6,8	16,6
4,0	7,7	18,7
5,0	8,4	20,6
6,0	8,9	22,3
7,0	9,3	23,6
8,0	9,6	24,5
9,0	9,9	25,3
10,0	10,2	26,0

