

# TM.PRIMO PPZ 40D 180 M AT



|                                               |                                                          |
|-----------------------------------------------|----------------------------------------------------------|
| Catalog number                                | TM-PZ.40D.AT03B                                          |
| Duration time                                 | 3 h                                                      |
| Operating mode                                | M                                                        |
| Version                                       | AT - auto-test / self-test                               |
| Colour                                        | RAL9005                                                  |
| Visibility                                    | 40 m                                                     |
| Luminance                                     | >500 cd/m²                                               |
| Active power                                  | 6.63 W                                                   |
| Power supply                                  | 210÷250 V AC 50÷60 Hz                                    |
| Power supply CB                               | 186÷254 V DC                                             |
| Dimming mode                                  | no                                                       |
| Temperature range                             | 5-40 °C                                                  |
| Material                                      | metal                                                    |
| Insulation class                              | 1                                                        |
| IP                                            | IP20                                                     |
| IK                                            | IK07                                                     |
| Battery                                       | LiFePO4/C 6.4V 1.5Ah                                     |
| Warranty                                      | 24 months - ST<br>36 months - AT<br>60 months - DATA, CB |
| versions                                      | D - <b>double-sided fitting</b>                          |
| available sections of hang the luminaires are | standard: 500<br>option: 250, 1000                       |
| Application                                   | escape route direction                                   |

