

# TM.ONTEC S20 M1U 60 NM ST



|                   |                                                          |
|-------------------|----------------------------------------------------------|
| Catalog number    | TM-S2.MUSTN140W                                          |
| Application       | anti-panic lighting                                      |
| Duration time     | 1 h                                                      |
| Operating mode    | NM                                                       |
| Version           | ST – for button test                                     |
| Colour            | RAL9003                                                  |
| Luminous flux     | 125 lm                                                   |
| Active power      | 1.95 W                                                   |
| Power supply      | 210+250 V AC 50+60 Hz                                    |
| Power supply CB   | 186+254 V DC                                             |
| Dimming mode      | no                                                       |
| Temperature range | 5-40 °C                                                  |
| Material          | PC                                                       |
| Insulation class  | 2                                                        |
| IP                | IP44/IK08                                                |
| IK                | IK08                                                     |
| Battery           | LiFePO4/C 3.2V 1.5Ah                                     |
| Warranty          | 24 months - ST<br>36 months - AT<br>60 months - DATA, CB |



PHOTOMETRY [m]

| Ceiling height | Distance wall - fitting | Distance fitting - fitting |
|----------------|-------------------------|----------------------------|
| 2,5            | 3,5 - 1h   3,0 - 3h     | 7,0 - 1h   8,0 - 3h        |
| 3,0            | 3,5 - 1h   3,5 - 3h     | 9,5 - 1h   8,0 - 3h        |
| 4,0            | 4,5 - 1 h   4,0 - 3h    | 11,5 - 1 h   9,5 - 3h      |
| 5,0            | 5,0 - 1h   4,0 - 3 h    | 13,0 - 1 h   11,0 - 3 h    |
| 6,0            | 5,0 - 1 h   3,5 - 3h    | 15,0 - 1 h   12,5 - 3h     |
| 7,0            | 5,0 - 1h   3,5 - 3h     | 16,5 - 1 h   13,5 - 3h     |
| 8,0            | 5,5 - 1 h   3,5 - 3h    | 18,0 - 1 h   14,0 - 3h     |
| 9,0            | 5,5 - 1h   3,0 - 3h     | 19,0 - 1h   14,5 - 3h      |
| 10,0           | 5,5 - 1 h   2,0 - 3h    | 20,0 - 1h   15,0 - 3h      |

