

# TM.ONTEC S20 M2X CB+



|                   |                                                          |
|-------------------|----------------------------------------------------------|
| Catalog number    | TM-S2.MXCB+060W                                          |
| Application       | anti-panic lighting                                      |
| Duration time     | 0 h                                                      |
| Operating mode    | -                                                        |
| Version           | CB+                                                      |
| Colour            | RAL9003                                                  |
| Luminous flux     | 154 (L); 309 (H) lm                                      |
| Active power      | 4.4 W                                                    |
| Power supply      | 210+250 V AC 50+60 Hz                                    |
| Power supply CB   | 186+254 V DC                                             |
| Dimming mode      | no                                                       |
| Temperature range | -15-55 °C                                                |
| Material          | PC                                                       |
| Insulation class  | 2                                                        |
| IP                | IP65/IK08                                                |
| IK                | IK08                                                     |
| Battery           | Un[V] DC 186-254                                         |
| Warranty          | 24 months - ST<br>36 months - AT<br>60 months - DATA, CB |



PHOTOMETRY [m]

| Ceiling height | Distance wall - fitting | Distance fitting - fitting |
|----------------|-------------------------|----------------------------|
| 2,5            | 3,0 - CB L   3,5 - CB H | 7,0 - CB L   8,0 - CB H    |
| 3,0            | 3,5 - CB L   3,5 - CB H | 8,0 - CB L   9,0 - CB H    |
| 4,0            | 4,0 - CB L   4,5 - CB H | 9,5 - CB L   11,0 - CB H   |
| 5,0            | 4,0 - CB L   5,0 - CB H | 11,0 - CB L   12,5 - CB H  |
| 6,0            | 3,5 - CB L   5,0 - CB H | 12,5 - CB L   14,5 - CB H  |
| 7,0            | 3,5 - CB L   5,0 - CB H | 13,5 - CB L   16,0 - CB H  |
| 8,0            | 3,5 - CB L   5,5 - CB H | 14,0 - CB L   17,0 - CB H  |
| 9,0            | 3,0 - CB L   5,5 - CB H | 14,5 - CB L   18,0 - CB H  |
| 10,0           | 2,0 - CB L   5,0 - CB H | 15,0 - CB L   19,0 - CB H  |

